ASSEMBLING THE SYSTEM


SILENT



Unroll and extend the base mat

After verifying that the subfloor is clean and leveled, proceed with laying the SILENT soundproofing mat on the entire floor area.

KERLITE COTTOD'ESTE



Lay the Kerlite slabs

Then lay the Kerlite slabs, chosen among the colours available in the 5plus and 6plus versions, directly on the mat without the use of adhesives.



Seal the grout lines

After having laid KERLITE on the floor, it is necessary to seal the spaces between the slabs with FILLER.

Once dry, this sealant guarantees a perfect walkable and waterproof surface.

KERLITE EASY OFFERS TWO EXCLUSIVE SOLUTIONS FOR GROUT LINE FINISHES

FILLER FAST



Easy and quick to apply for a pedestrian floor in just a few hours. Its matte finish makes it perfect for modern

FILLER ARDEX SC MATT



Easy and quick to apply for a pedestrian floor in just a few hours. The remarkable textured look makes it ideal for high-end surfaces.



COTTODESTE EXCLUSIVE SURFACES



FLOATING FLOOR SYSTEM

WHAT IS IT

Kerlite Easy is the FIRST dry laying installation system without adhesives certified and patented with Kerlite Plus. It is installed without mortar and, thanks to the exclusive use of fibreglass-reinforced Kerlite slabs, it is more durable than any other traditional laying system.

With a thickness of only 7 mm, this system is used for the installation of a new kind of highly durable porcelain stoneware flooring that is perfect for interior RESIDENTIAL or LIGHT COMMERICAL use.

It is possible to renovate without demolishing as it can be laid on pre-existing floors.

KERLITE EASY is unique, because it uses a high-performance product: laminated porcelain stoneware Kerlite slabs, exactly as they are when they exit the production line. This means no subsequent processing and the guarantee of a quality manufacturing process tested by Cotto d'Este in over 15 years of experience and with millions of square meters sold worldwide.

Cotto d'Este guarantees for 10 years the resistance to wear of Kerlite ceramic slabs, the integrity of the Silent matting, and the functional characteristics of the Filler sealant, if installed in interior environments for residential or light commercial use.





cottodeste.it - blustyle.it

PANARIAGROUP INDUSTRIE CERAMICHE S.p.A.

KERLITE easy

PRIMARY INTENDED USE





STANDS



WHO IS IT FOR

Retailers of ceramic materials

To create new sales opportunities with both business to business clients and end-users.

Installers

To have access to a new high-quality solution when it is necessary to work quickly, using a product with high aesthetic value. KERLITE EASY is the perfect system with which to preserve, if necessary, the underlying floor.

Designers

To offer clients a high quality solution when they need a job done quickly, using a range that provides the utmost aesthetic value. KERLITE EASY is the perfect system for preserving, when necessary, the old underlying floor.

End-user

To have a new and highly attractive floor in very little time, without the inconvenience of demolishing the old floor, thus significantly reducing the costs of installation and without having to raise the doors. This solution also significantly reduces impact and footfall noise towards the lower floor.

AN OUTSTANDING SOLUTION



Superior durability The secret of KERLITE EASY is Kerlite.

Because only with Kerlite does the system

guarantee the utmost reliability. Tests conducted on flooring created with the KERLITE EASY system have shown that the combination of the SILENT mat and the compactness of KERLITE combined to its fibreglass reinforcement provide a degree of durability that is superior to the standards

ceramic tiles.

All of this is further enhanced by the exclusive benefit of a drastic reduction in footfall noise.

offered by ordinary flooring with adhered

KERLITE easy

EXCLUSIVE BENEFITS

The fibreglass mesh on the

reverse side of Kerlite slabs

SILENT mat and the FILLER

sealant ensure the utmost

resistance and stability

combined with the use of the



Practical

Lightweight

With a weight of only

the existing structure.

13 kg/m² one can have a new


porcelain stoneware floor without weighing down

Makes it possible to create an overlying ceramic surface without demolishing the old floor.



Certified

Compliant with the strict American standard for flooring ASTM C627 (ROBINSON TEST).



Waterproof

waterproof.

With the combined

use of Kerlite slabs and

FILLER sealant, the floor is

guaranteed to be entirely

Easy

to the floor.

Stable

KERLITE EASY uses a new laying method for ceramic tiles which is a consolidated system that is already commonly used for other laminated products.



Affordable

Provides significant savings as compared to a standard renovation.



More Attractive

Makes it possible to create a floor without expansion joints.



Fast

It is straightforward and quick to install.



Environmentally Sustainable

Makes it possible to periodically replace the materials and reuse them in other environments.



It is soundproof: thanks to the

16 times more than ordinary adhered ceramic tile floors.



Large-sized laminated porcelain stoneware reinforced with fibreglass:

a light, resistant and versatile product for new design perspectives in the world of architecture and housing.

HIGHEST STANDARDS IN OUALITY AND PERFORMANCE Thanks to the use of the best raw materials

HIGHLY COMPACT AND ELASTIC SLABS

Thanks to a unique pressing process

EXCELLENT AESTHETIC LOOK OF THE PRODUCTS

Thanks to exclusive surface processing technologies

EXTRAORDINARY ADDED RESISTANCE Thanks to the reinforcing fibreglass mesh

HIGHLY ECO-FRIENDLY Less raw materials used, lower water and energy

consumption and lower CO₂ emissions

Kerlite Easy is applicable on most of the formats of the Kerlite range (over 140 items)

KERLITE combined action of the SILENT mat and Kerlite. COTTO D'ESTE It reduces footfall noise to the lower floor by approximately